

Bambach Saddle Seat®

Assembly Instructions



Bambach Saddle Seat® with(out) back rest

Bambach Saddle Seat with back rest



How to mount the seat

- Position the hole at the bottom of the seat above the upper end of the gas lift (Fig. 6).
- Slide the seat surface to the upper end of the gas lift (Fig. 7 and 8).
- Sit on the seat to create a firm connection between the seat and the gas lift.



Fig. 6



Fig. 7



Fig. 8

How to mount the castors

- Insert the castors into the base (Fig. 1)
- Then place the base on the ground with the castors facing downwards (Fig. 2).



Fig. 1



Fig. 2

How to insert the hydraulic gas lift

- Insert the gas lift in the opening of the five-arm base (Fig. 3)



Fig. 3

How to mount the optional foot ring

- Place the foot ring onto the gas lift and fix it with the knurled screw at the desired height (Fig. 4 and 5)



Fig. 4



Fig. 5

How to mount the back rest

- Loosen the side-mounted screw without unscrewing it completely
- Slightly bend the bottom of the plastic cover. This exposes the end of the back rest shell and you can now guide the back rest stem through the space provided. Insert the plastic cover over the end of the back rest support, set the seat back to the desired height and secure it by turning the lateral screw (Fig. 9, 10, 11).



Fig. 9



Fig. 10



Fig. 11

Bambach Saddle Seat® – How to adjust the sitting position

1. Seat

- Sit on the back of the seat (Fig. 1)



Fig. 1

2. Height

- Use the lever on the right-hand side of the seat to adjust its height as desired. Your knees should be at an angle of 30 – 45 degrees (Fig. 2).



Fig. 2

3. Inclination

- Adjust the desired inclination of the seat by pulling the right rear lever (Fig. 3 – 5).

Tilted forward



Fig. 3

Centred



Fig. 4

Tilted backward



Fig. 5

4. Back rest

- Adjust the desired angle of inclination of the back rest by pulling the left lever. Then push the lever down to lock the desired position. Use the screw on the right side to adjust the height of the back rest (Fig. 6).



Fig. 6



Caution:

If the center of gravity is shifted or if it is used improperly, there is a risk of injury from the chair tipping over.

How to attach an armrest (left or right*)

To assemble an armrest is an easy task. By doing this yourself, you will be able to find the optimum height and positioning of the back rest with respect for your normal sitting position. You can also ensure that you are seated comfortably and well supported.



1. Remove the seat and cradle from the height adjustment.

- Upend the seat and keep it stable.
- Position the special tool parallel to the gas lift so that it lies on the cradle (Fig. 1 and 2).
- The special tool allows you to remove the top of the seat without causing any damage.
- Use a hammer to hit the end of the tool until the top comes off the gas lift (Fig. 3 and 4).
- Should your Bambach seat already be a bit older, the seat will be firmly connected to the gas lift and require a few solid hits.



Fig. 1



Fig. 2



Fig. 3



Fig. 4

How to attach an armrest (left or right*) - *continued*

2. Place the spacer on the height adjustment approximately 13 cm below the tip of the stem and fix it with an Allen key.

- Make sure that the spacer is at least 13 cm below the tip of the gas lift (Fig. 5).
- Ensure that the spacer is not more than 5 cm from the bottom of the gas lift to maintain the flexibility of the height adjustment - how far down you attach the spacer to the height adjustment will directly affect the adjustability you can achieve with the seat height (Fig. 6).
- To determine the appropriate height of the spacer, bring the seat to the height you normally use for sitting. Select the height of the spacer so that you have a comfortable and supportive height. The height of the armrest can be adjusted by using the knob on the side of the back rest.

3. Place the mounting arm on the gas lift (Fig. 7 and 8).

4. Mount the armrest to the mounting arm and adjust it to the desired height using the armrest height adjuster (2) and fix it in place.

5. Put the seat back onto the gas lift.

6. You can then make the remaining adjustments using the shift lever (1) and find the most comfortable position/angle.



Fig. 5



Fig. 6



Fig. 7



Fig. 8

Genuine Leather Care

- The new Bambach Saddle Seat brings a new, initially unfamiliar sitting posture with it.
- It may take a few days for you to get used to the new seating position.
- For the first few days, we recommend gradually increasing your sitting time on the Bambach.
- Some initial muscle ache may be experienced as some muscles start to work and others are relieved. After the acclimatisation you will relax and enjoy your new freedom of movement!

Important

- Please only clean the leather with a damp cloth. Do not use conventional disinfectants! These may aggressively affect the leather and cause damage! Please only use a disinfectant without alcohol.
- Once or twice a week, after cleaning and disinfecting, rub the leather surface thoroughly with the Bambach leather care oil and leave it on overnight. Remove any remaining excess with a dry cloth. This way, the leather stays soft in the long term and you avoid rapid wear and eventual cracking.

Please note

- On light leather, dark clothing may cause discolouration on the leather!



Duisburg, Germany
Tel.: +49 (203) 99269-888
Fax: +49 (203) 299283
Email: info@hagerwerken.de



China
Tel.: +852-2622 2795
Fax: +852-2622 2503
Email: info@hagerasia.com.hk



Moscow, Russia
Tel. / Fax: +7 495 255 0902
Email: o.seifert@hagerwerken.de



Wroclaw, Poland
Tel.: +48-71-368 71 66
Fax: +48-71-368 10 21
Email: biuro@hager.com.pl