

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Luxatemp Glaze and Bond

Revision date: 24.01.2020

Product code: 2500

Page 1 of 6

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Luxatemp Glaze and Bond

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.3. Details of the supplier of the safety data sheet**

Company name:	DMG Chemisch-Pharmazeutische Fabrik GmbH	
Street:	Elbgaustraße 248	
Place:	D-22547 Hamburg	
Telephone:	+49. (0) 40. 84006-0	Telefax: +49. (0) 40. 84006-222
e-mail:	info@dmg-dental.com	
Internet:	www.dmg-dental.com	

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1B

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

Harmful to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No 1272/2008**

Signal word: Danger

Pictograms:

**Hazard statements**

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P501	Dispose of waste according to applicable legislation.
P302+P352	IF ON SKIN: Wash with plenty of water.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Luxatemp Glaze and Bond

Revision date: 24.01.2020

Product code: 2500

Page 2 of 6

smoking.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

chemical characterization (preparation): Acrylate.-resin.:

MMA (CAS 80-62-6): 40-50 %

DPPA (CAS 1384855-91-7): 30-40 %

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
80-62-6	MMA			< 50 %
	201-297-1	607-035-00-6		
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H317 H335			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****After inhalation**

Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

After contact with skin, wash immediately with: Water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

Medical treatment necessary.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**Extinguishing powder. Sand. Foam. Carbon dioxide (CO₂).**Unsuitable extinguishing media**

High power water jet.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Luxatemp Glaze and Bond

Revision date: 24.01.2020

Product code: 2500

Page 3 of 6

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Wear suitable gloves.
Avoid contact with eyes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.
Use explosion-proof machinery, apparatus, ventilation facilities, tools etc.

Advice on general occupational hygiene

When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
80-62-6	Methyl methacrylate	50	-		TWA (8 h)	
		100	-		STEL (15 min)	

Additional advice on limit values

exposure limit values: (MMA): 210 mg/m³; 50 ml/m³

8.2. Exposure controls**Appropriate engineering controls**

Ensure adequate ventilation of the storage area.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Tightly sealed safety glasses.

Hand protection

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

Respiratory protection

Filtering device (full mask or mouthpiece) with filter: A

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid	
Colour:	yellow	
Odour:	ester	
Lower explosion limits:		2,1 vol. %
Upper explosion limits:		12,5 vol. %

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Luxatemp Glaze and Bond

Revision date: 24.01.2020

Product code: 2500

Page 4 of 6

Flash point:	Mixture not tested.
Auto-ignition temperature:	> 430 °C
pH-Value:	not applicable
Vapour pressure: (at 20 °C)	40 hPa
Density:	ca. 1,1 g/cm ³
Relative vapour density:	> 1
point of decomposition:	> 100 °C

SECTION 10: Stability and reactivity**10.4. Conditions to avoid**

heat. Light.

Decomposition takes place from temperatures above: 100 °C

10.5. Incompatible materials

Keep away from strong acids, leachates, heavy metal salts and reducing materials.

10.6. Hazardous decomposition products

In case of fire may be liberated: Gas / vapours, irritant. (Acrylate., pungent)

Further information

Substances sensitive to light.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

LD50, oral (rat): > 2800 mg/kg (calculated, ATE mix)

Irritation and corrosivity

Irritant effect on the eye: In rare cases the product can cause temporary erythema of the skin.

Frequently or prolonged contact with skin may cause dermal irritation.

Sensitising effects

May cause sensitization by skin contact.

Specific effects in experiment on an animal

LD50: (Rat)

> 5.000 mg/kg

Additional information on tests

Contains Methyl methacrylate.: May produce an allergic reaction.

May cause sensitization by skin contact.

SECTION 12: Ecological information**12.1. Toxicity**

Product is partially biodegradable. >50 %

Acute fish toxicity LC50: > 79 mg / l / 96 h

12.2. Persistence and degradability

Preparation not tested.

Do not allow to enter into surface water or drains.

Leakage into the environment must be prevented.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Luxatemp Glaze and Bond

Revision date: 24.01.2020

Product code: 2500

Page 5 of 6

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

List of Wastes Code - residues/unused products

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (EXCEPT KITCHEN AND RESTAURANT WASTES NOT ARISING FROM IMMEDIATE HEALTH CARE); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing hazardous substances; hazardous waste

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number: UN 1247
14.2. UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Classification code: F1
 Limited quantity: 1 L
 Transport category: 2
 Hazard No: 339
 Tunnel restriction code: D/E

Other applicable information (land transport)

E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1247
14.2. UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Special Provisions: -
 Limited quantity: 1 L
 EmS: F-E, S-D

Other applicable information (marine transport)

E2

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1247
14.2. UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Luxatemp Glaze and Bond

Revision date: 24.01.2020

Product code: 2500

Page 6 of 6



Limited quantity Passenger:	1 L	
IATA-packing instructions - Passenger:		353
IATA-max. quantity - Passenger:		5 L
IATA-packing instructions - Cargo:		364
IATA-max. quantity - Cargo:		60 L

Other applicable information (air transport)

E2

: Y341

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):
Entry 40, Entry 75

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information**Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

Further Information

-

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)