

Safety Data Sheet

according to UK REACH Regulation

sili spray Adhesive

Revision date: 19.07.2023

Product code: 10109

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

sili spray Adhesive

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesive for use in dentistry.

1.3. Details of the supplier of the safety data sheet

Company name:	DETAX GmbH	
Street:	Carl-Zeiss-Straße 4	
Place:	D-76275 Ettlingen	
Telephone:	+49 7243/510-0	Telefax: +49 7243/510-100
E-mail:	post@detax.com	
Internet:	www.detax.com	
Responsible Department:	This number is only obtainable during office hours (Monday - Thursday 8.00 a.m. - 5.00 p.m., Friday 8.00 a.m. - 4.00 p.m.)	

1.4. Emergency telephone number:

+1-800-424-9300 (CHEMTREC worldwide)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Aerosol 1; H222-H229
Asp. Tox. 1; H304
Skin Irrit. 2; H315
Eye Irrit. 2; H319
STOT SE 3; H336
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

C6-7 - Hydrocarbons
ethyl acetate
methyl acetate

Signal word: Danger**Pictograms:****Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Safety Data Sheet

according to UK REACH Regulation

sili spray Adhesive

Revision date: 19.07.2023

Product code: 10109

Page 2 of 10

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Additional advice on labelling

According to Regulation (EC) 1272/2008, art.1 No. 5 (d) this product as a medical product must not be labelled!

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Organic solvent in propellant (liquefied butane gas)

Hazardous components

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	Classification (GB CLP Regulation)	
92128-66-0	C6-7 - Hydrocarbons	5 - < 20 %
	921-024-6	01-2119475514-35
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411	
141-78-6	ethyl acetate	5 - < 20 %
	205-500-4	607-022-00-5
	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066	
79-20-9	methyl acetate	0.1 - < 5 %
	201-185-2	607-021-00-X
	02-2119752526-34	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
141-78-6	205-500-4	ethyl acetate	5 - < 20 %
		inhalation: LC50 = >29,3 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg	
79-20-9	201-185-2	methyl acetate	0.1 - < 5 %
		inhalation: LC50 = 49-98 mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

Safety Data Sheet

according to UK REACH Regulation

sili spray Adhesive

Revision date: 19.07.2023

Product code: 10109

Page 3 of 10

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water. Do not induce vomiting. If you feel unwell, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

Water.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

Safety Data Sheet

according to UK REACH Regulation

sili spray Adhesive

Revision date: 19.07.2023

Product code: 10109

Page 4 of 10

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not pierce or burn, even after use. If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Do not store with flammable liquids, flammable solid substances or desensitised substances, spontaneously flammable substances, substances liberating flammable gases in contact with water, combustible liquids.

Further information on storage conditions

Keep only in the original container in a cool, dry and well-ventilated place, away from foodstuffs.

7.3. Specific end use(s)

Aerosol for better adhesion of condensation curing dental impression materials on impression trays.
For use by trained specialist staff.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
141-78-6	Ethyl acetate	200	734		TWA (8 h)	WEL
		400	1468		STEL (15 min)	WEL
79-20-9	Methyl acetate	200	616		TWA (8 h)	WEL
		250	770		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.

Safety Data Sheet

according to UK REACH Regulation

sili spray Adhesive

Revision date: 19.07.2023

Product code: 10109

Page 5 of 10

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Suitable are gloves of the following material: Butyl caoutchouc (butyl rubber) , FKM (fluoro rubber)

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing .

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquefied gas with liquid and solid parts, compressed
Colour:	blue
Odour:	faintly like esters

Test method

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Flammability:	not applicable
Lower explosion limits:	1,5 vol. %
Upper explosion limits:	8,5 vol. %
Flash point:	<-10 °C DIN 51755
Auto-ignition temperature:	365 °C DIN 51794
Decomposition temperature:	not determined
pH-Value:	not determined
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.
Solubility in other solvents	not determined
Partition coefficient n-octanol/water:	not determined
Vapour pressure: (at 70 °C)	9000 hPa
Density (at 15 °C):	0,74 g/cm ³ DIN 51757
Relative vapour density:	not determined

9.2. Other information

Information with regard to physical hazard classes

Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Oxidizing properties	
Not oxidizing.	

Other safety characteristics

Evaporation rate:	not determined
Solid content:	not determined

SECTION 10: Stability and reactivity

Safety Data Sheet

according to UK REACH Regulation

sili spray Adhesive

Revision date: 19.07.2023

Product code: 10109

Page 6 of 10

10.1. Reactivity

Extremely flammable aerosol.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Reacts with : flammable, spontaneously flammable and combustible substances. Prevent any contact of the product with strong oxidising agents, such as chlorine or concentrated oxygen.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Higher temperatures advance the formulation of explosive vapour-air mixtures, therefore don't expose the product to increased temperatures.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

The following applies for the silicone content of the product: At temperature of appr. 150°C/ 302 °F a small amount of formaldehyde can be released by oxidative degradation.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
141-78-6	ethyl acetate				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 >29,3 mg/l	Rat		
79-20-9	methyl acetate				
	oral	LD50 >5000 mg/kg	Rat	GESTIS	
	dermal	LD50 >5000 mg/kg	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50 49-98 mg/l	Rat		

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to UK REACH Regulation

sili spray Adhesive

Revision date: 19.07.2023

Product code: 10109

Page 7 of 10

STOT-single exposure

May cause drowsiness or dizziness. (C6-7 - Hydrocarbons; ethyl acetate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
141-78-6	ethyl acetate					
	Acute fish toxicity	LC50 >100 mg/l	96 h	Salmo trutta fario (L) (Freshwater trout)	OECD 203	
	Acute algae toxicity	ErC50 >100 mg/l	72 h	Desmodesmus subspicatus	OECD 201	
	Acute crustacea toxicity	EC50 >100 mg/l	48 h	Daphnia magna (Big water flea)		
79-20-9	methyl acetate					
	Acute fish toxicity	LC50 320 mg/l	96 h	Pimephales promelas (fathead minnow)		
	Acute algae toxicity	ErC50 >120 mg/l	72 h	Desmodesmus subspicatus	OECD 201	
	Acute crustacea toxicity	EC50 1027 mg/l	48 h	Daphnia magna (Big water flea)	OECD 202	

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
141-78-6	ethyl acetate				
	OECD 301D/ EEC 92/69/V, C.4-E	>70%	28		

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
141-78-6	ethyl acetate	0,68

BCF

CAS No	Chemical name	BCF	Species	Source
141-78-6	ethyl acetate	30	Leuciscus idus (golden orfe)	

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

Safety Data Sheet

according to UK REACH Regulation

sili spray Adhesive

Revision date: 19.07.2023

Product code: 10109

Page 8 of 10

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

Not identified as PBT/ vPvB substances

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number or ID number:</u>	UN 1950
<u>14.2. UN proper shipping name:</u>	AEROSOLS
<u>14.3. Transport hazard class(es):</u>	2
<u>14.4. Packing group:</u>	-
Hazard label:	2.1
Classification code:	5F
Limited quantity:	1 L/ 30 kg
Transport category:	2
Tunnel restriction code:	D

Other applicable information (land transport)

Flammable gas

Marine transport (IMDG)

<u>14.1. UN number or ID number:</u>	UN 1950
<u>14.2. UN proper shipping name:</u>	AEROSOLS
<u>14.3. Transport hazard class(es):</u>	2.1
<u>14.4. Packing group:</u>	-
Hazard label:	2.1
Marine pollutant:	-
Limited quantity:	1000 mL/ 30 kg
EmS:	F-D, S-U

Other applicable information (marine transport)

Flash point: <-10°C c.c.

Air transport (ICAO-TI/IATA-DGR)

<u>14.1. UN number or ID number:</u>	UN 1950
<u>14.2. UN proper shipping name:</u>	AEROSOLS, flammable
<u>14.3. Transport hazard class(es):</u>	2.1
<u>14.4. Packing group:</u>	-
Hazard label:	2.1
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203

Safety Data Sheet

according to UK REACH Regulation

sili spray Adhesive

Revision date: 19.07.2023

Product code: 10109

Page 9 of 10

Excepted quantity:	E0	
IATA-packing instructions - Passenger:		203
IATA-max. quantity - Passenger:		75 kg
IATA-packing instructions - Cargo:		203
IATA-max. quantity - Cargo:		150 kg

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 75

Additional information

Aerosol Directive (75/324/).

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
Flam. Gas: Flammable gases
Aerosol: Aerosols
Flam. Liq: Flammable liquids
Asp. Tox: Aspiration hazard
Skin Irrit: Skin irritation
Eye Irrit: Eye irritation
STOT SE: Specific target organ toxicity - single exposure
Aquatic Chronic: Chronic aquatic hazard

Safety Data Sheet

according to UK REACH Regulation

sili spray Adhesive

Revision date: 19.07.2023

Product code: 10109

Page 10 of 10

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Bridging principle "Aerosols"
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)